

AFTER TILE GROUT FILM REMOVER



Colour	Product Code	Pack Size	Box Qty
Clear/Pale Green	ATGRTREM1	1LTR	12

Product Description

Grout Film Remover is a citric acid based formula designed for the removal of wet and cured grout, limescale, adhesive residue and cement film on newly laid and existing glazed floor and wall tiles without causing damage to the grout or tiles. Grout Film Remover dissolves and removes ingrained dirt and unlike hydrochloric acid based products it can be safely used on most metal surfaces such as tools and tiling equipment.

Grout Film Remover is a highly concentrated formula that can be diluted up to 10 times with water dependent on the levels of deposits on the tiles. It is a safe product (transport and storage) that is also fully biodegradable.

Benefits

- Removes wet & cured grout, limescale, adhesive residue and cement based adhesives from porous and non-porous tiles
- Biodegradable, safer formula
- Easily removes ingrained dirt without damaging the grout
- Ideal for use on walls, floors and tools.
- For interior and exterior use

Areas For Use

- Bathrooms
- Shower areas
- Kitchen areas
- External Tiled areas.

Limitations

- **Always test a small inconspicuous area prior to full application.**
- Do not use on Marble, granite or travertine.
- Do not use on coloured cement based grouts.
- Do not use on soft metals such as lead brass, copper or aluminium.
- Avoid splashes or spills on sensitive surface such as brass, copper, stainless steel and aluminium. Remove any excess material or spills immediately with clean fresh water.
- It is the user's responsibility to determine suitability for use. If in doubt contact technical services for advice.

Application

Always check compatibility at correct dilution level by testing an inconspicuous area prior to full scale use. Not suitable for use on coloured grouts. Always wear suitable latex/rubber gloves.

Mask off surrounding areas to avoid splashes or spills particularly in areas where soft metals are present such as brass, copper, anodised trims and lead.

For removing general dirt/grime and light grout films, dilute 1 part Grout Film Remover to 9 parts water and apply using a cloth or sponge. Wipe using a clean cloth or sponge with fresh water.

For heavier grout film deposits, medium adhesive and cement residues dilute 1 part Grout Film Remover to 2 parts water and apply as above.

Dilute 1-1 where heavier adhesive deposits of adhesive or cement are present. Clean with fresh water.

Use neat for cleaning tools and equipment.

For all applications always clean surfaces with fresh water after application of Grout Film Remover.

Specific Data

Appearance	Clear/Pale green liquid
Application Temp	5°C to 35°C
S.G	1.09-1.13g/cm ³
pH	0.5 – 1.0
Coverage	Approx. 10m ² per litre of diluted product depending on porosity of substrate. See full dilution guide above.

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store in cool, dry conditions between + 5 and + 25°C. PROTECT FROM FROST. Storage outside these parameters will dramatically reduce shelf life.

Shelf Life

24 months from date of manufacture in original unopened containers.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.