

Technical Data Sheet Rev.1

EVERBUILD Stick 2 Epoxy Putty Aqua – 50 gm

DESCRIPTION AND USES

Everbuild Stick 2 Epoxy Putty Aqua is a 2 component epoxy based putty for permanent repairs to damp, wet areas and underwater repairing, bonding, sealing, fixing, remoulding and rebuilding virtually any material. (with limitations). . It can be applied underwater, both fresh and salt, and will bond to substrates such as fibreglass, metal, wood, concrete, ceramic, glass etc. Mixes in one minute. Totally waterproof once dried.

APPLICATION (we always recommend gloves be worn when handling this product)

Surfaces must be clean, sound and free of oil and grease. Smooth surfaces should be abraded. Break off the required amount of EPOXY PUTTY AQUA and mix by hand to a uniform colour. Apply to required areas immediately. Fill all voids and holes, apply pressure on damp, wet or slowly leaking surfaces. For a smooth appearance, handrub with water or a damp cloth prior to hardening. Allow to fully cure before sanding or machining.

Working time from mixing – 5 minutes @ 20°C

Curing time – 60 minutes @ 20°C

STORAGE

Store in cool dry conditions between 0 and 20°C. Storage outside these parameters will dramatically reduce shelf life.

Shelf life – 3 years from date of manufacture in original unopened containers.

HEALTH AND SAFETY

See safety data sheet

LIMITATIONS

Will not stick polyethylene, polypropylene, or PTFE

Do not use on bitumen, asphalt.

Do not use as a mirror adhesive as the product may attack the mirror backing.

Do not use below 5°C.

As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability of use. If in doubt, contact Technical Services Department for advice.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application.

Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that

The information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with

The stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information

Provided verbally by telephone to any prospective or existing customer.

Everbuild Building Products Ltd

Site 41, Knowsthorpe Way

Cross Green Industrial Estate

Leeds LS9 0SW

England

Tel: 0113 240 3456

Fax: 0113 240 0024

www.everbuild.co.uk