



Site 41, Knowsthorpe Way,
Cross Green Industrial Estate, Leeds, LS9 0SW
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

# CONSTRUCTION PRODUCTS REGULATION DECLARATION OF PERFORMANCE

No: 225/1-CPR/ 2014

1. Identification Code	EVERFLEX 225 Industrial & Glazing Silicone
1. Identification code	EVEN LEX LES MOUSTING & GIVENING SINCOINC
	Codes: 225
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings
	and pedestrian walkways Part 1: Sealants for Façade
	elements
4. Manufacturer	Everbuild Building Products ltd, Site 41, Cross Green
	Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy	System 3
of Performance	
7. Notified Body and Tasks	SKZ Notified Body No. 1213
8. European Technical Assessment	Not Applicable
9. Declared Performance	TO EN15651-1 (2012)
Туре	F EXT-INT-CC
Classification	F12.5E
Reaction to Fire	Class F
Loss of Volume ISO10563	≤40%



Site 41, Knowsthorpe Way,
Cross Green Industrial Estate, Leeds, LS9 0SW
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

	Website. WWw.sverbuild.co.uk
Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	NF
Adhesion/cohesion properties (-30°C)	NF
Durability	Pass

1. Identification Code	EVERFLEX 225 Industrial & Glazing Silicone
	Codes: 225
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings
	and pedestrian walkways Part 2: Sealants for
	Glazing elements
4. Manufacturer	Everbuild Building Products ltd, Site 41, Cross Green
	Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy	System 3
of Performance	
7. Notified Body and Tasks	SKZ Notified Body No. 1213
8. European Technical Assessment	Not Applicable
9. Declared Performance	TO EN15651-2 (2012)
Туре	G-CC
Classification	G20LM



Site 41, Knowsthorpe Way,
Cross Green Industrial Estate, Leeds, LS9 0SW
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

	website: www.everbuild.co.uk
Reaction to Fire	Class F
Loss of Volume ISO10563	≤40%
Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	NF
Adhesion/cohesion properties after exposure to heat, water and artificial light ISO 11431	NF
Elastic recovery ISO 7389	≥60%
Adhesion/cohesion properties (-30°C) ISO 8339 modified	NF
Adhesion/cohesion properties at maintained extension (-30°C) ISO 8340	NF
Durability	Pass

1. Identification Code	EVERFLEX 225 Industrial & Glazing Silicone
	Codes: 225
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings
	and pedestrian walkways Part 3: Sealants for
	Sanitary elements
4. Manufacturer	Everbuild Building Products ltd, Site 41, Cross Green
	Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy	System 3



Site 41, Knowsthorpe Way,
Cross Green Industrial Estate, Leeds, LS9 0SW
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

	website: www.everbuild.co.uk
of Performance	
7. Notified Body and Tasks	SKZ Notified Body No. 1213
8. European Technical Assessment	Not Applicable
9. Declared Performance	TO EN15651-3 (2012)
Туре	S
Classification	S1
Reaction to Fire	Class F
Loss of Volume ISO10563	≤40%
Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	NF
Action of the microorganisms : Intensity of growth ISO 846, method B	1
Durability	Pass

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I.

I. G. Southerington – Head of Technical

P.R. Thomas – Technical Manager

Dated: Leeds, 3/4/14