

TECHNICAL DATASHEET

Plasterers Enhanced Grit Coat

Description & Uses

Plasterers Enhanced Grit Coat is a one coat, ready to use plaster bonding agent with added fine aggregate to provide a key to surfaces prior to plastering.

Easy to apply, by brush or roller, with an easily identifiable colour to ensure full coverage, it is ideal for use on surfaces such as plaster, concrete and difficult, low or non-porous substrates. For interior use

THE 1ST CHOICE FOR THE PROFESSIONAL PLASTERER

Benefits:

- Exceptional grit distribution for maximum performance and grip
- Contains fine aggregate to provide a key to smooth surfaces
- Easily identifiable colour to aid coverage Orange!
- Apply by roller or brush



Directions

- STIR WELL BEFORE USE
- Ready to use do not dilute the product.
- Ensure surfaces are sound, clean, dry and free from contaminates, such as loose or flaking material. Make sure that the background is sound and will provide sufficient support.
- Apply one coat, using either brush or roller, and leave to dry thoroughly for a minimum of 24 hours prior to plastering.
- Cold or humid conditions can increase the drying time. Ensure product is not used at temperatures below 5°
- It is the user's responsibility to dispose of all packaging correctly.

Coverage

Approximately 4-5m² / litre dependent on the porosity of the substrate.

Storage

Store in cool, dry conditions between +5°C and +30°C.



Shelf Life

24 months when stored in original, unopened packaging.

Limitations

- Do not use for external applications.
- As the manufacturer cannot know all the uses its products may be put to, it is the user's responsibility to determine suitability of use. If in doubt, please contact Technical Services department for advice. Safety Data available on request.

Technical Data

Colour	Orange

Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail info@cromar.uk.com.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products' are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.