## BlueSpot 10 PCE Bolt Remover Set (9-19mm) (01539)

## Best Practice Guide



The BlueSpot 10 PCE Bolt Remover Set is manufactured from heat-treated chrome-molybdenum for increased durability. Designed for the safe removal of bolts that have rounded off, rusted or painted over. Suitable for hand and power tools. Can be used with 3/8" breaker bar/ratchet and also has flats so that they can be used with spanners or wrenches. Complete with a useful carrying case for quick and easy storage.

Socket sizes - 9, 10, 11, 12, 13, 14, 15, 16, 17, 19mm



**ALWAYS** ensure you are wearing approved safety goggles and gloves whilst working with the bolt remover set.

- 1 Find the most suitable bolt remover from the set that is most similar in size to the damaged bolt you would like to remove from the vehicle.
- 2 Place the bolt remover over the damaged bolt.
- 3 Attach the bolt remover to the damaged bolt with a few short hammer blows.
- 4 With your wrench remove the bolt remover and damaged bolt from the vehicle.
- 5 Secure the bolt remover into a bench vice with the damaged bolt facing downwards towards the workbench.
- 6 Place the drift bar onto the damaged bolt through the bolt remover.
- 7 With a few short hammer blows the damaged bolt will release from the bolt remover.

