

bond it

Never compromise on quality!



DECKING OIL

Protective Barrier Oil for Timber Decking



WOODGUARD WOOD PROTECTION RANGE

Description:

A ready-to-use nourishing oil that feeds wood and restores the natural oils lost through weathering.

Benefits:

- ◆ Nourishes wood replacing natural oils.
- ◆ Resistant to UV light.
- ◆ Prevents mould and algae build up.
- ◆ Waterproofs preventing water ingress.
- ◆ Leaves a natural looking finish.
- ◆ Ready to use.
- ◆ For all types of garden decking.

Uses

WOOD GUARD DECKING OIL provides your deck with a natural looking protection by replacing natural oils in the wood. It provides a protective barrier against water penetration where constant weathering can cause swelling and warping. Suitable for use on untreated, previously oiled or weathered decking.

Preparation

New Decking: The timber should be allowed to weather for a minimum of 6 months before using DECKING OIL. Splash some drops of water onto the wood, if water sits on the surface in beads, then the decking does not require deck oil.

Old Decking: Use WOOD GUARD DECKING CLEANER to remove any dirt, grease, oil, mildew and other contaminants. Remove any loose or flaking material.



Application

Ensure that the decking is dry. Do not apply in wet conditions or if rain is imminent. Shake can thoroughly before use. Always test a small inconspicuous area prior to full application. Apply a flood coat using a good quality brush or roller. Apply a second coat once the first coat is dry (approx. 6 hours). Leave 24 hours before subjecting to foot traffic.

Clean Up: Clean brushes thoroughly in WHITE SPIRIT after use.

Note: Not for use on new wood DECKING OIL should only be used to restore and treat weathered timber.

Limitations

Do not traffic until fully cured. Do not apply in wet conditions or if rain is imminent. Do not use in temperatures below +5°C and above +30°C.

Coverage

5 Litres will give 2 coat coverage for approx. 20m² of decking.
2.5 Litres will give 2 coat coverage for approx. 10m² of decking.

Container Size

Available in 2.5 and 5L metal tins.

Colour

Pale brown coloured liquid.

Shelf Life

12 months from date of manufacture when stored in original sealed containers.

Storage Conditions

Store in cool, dry conditions in original sealed container between +5 and +25°C. Protect from frost.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Physical Properties	Pale brown liquid
Application Temperature Range	+5 to +30°C
Drying Time	6-24 hours depending on atmospheric conditions
Coverage Rate	2.5L will give 2 coat coverage for approx. 10m ² of decking
Cleaning	Rinse then wash brushes and rollers in white spirit
Shelf Life	1 year
UN Class	1263 Paint related material
UFI	2D20-200Q-D00H-XRP5



Product Details:

Code:	BDDOC5	BDDOC2
Colour:	Natural	Natural
Size:	5L	2.5L
Barcode:	5060021369772	5060021369789



Part of the Bond It Woodguard Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position.

Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001



BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V1 14/02/14
 Supersedes: V