Geo-Fix®

Reigns WHEN IT POURS



Easier & Faster

Geo-Fix All Weather is ready mixed and can simply be brushed into joints with minimal effort compared to using traditional mortar.

Geo-Fix All Weather can be applied in any weather conditions – even while it's raining!

Geo-Fix All Weather is easily finished by compacting with a pointing tool and used on joint widths of min 6mm and a minimum of 25mm deep.

Geo-Fix All Weather forms a solid joint that resists weed and plant growth, yet is permeable allowing water to escape to prevent ponding.

Available in 14kg packs in Natural Stone, Slate Grey and Anthracite.








The colours shown are as accurate as the limitations of the printing process allow. Please refer to actual product samples before purchasing.

How to use Geo-Fix®







Step 2 Sweep off the excess pools of standing water.



Step 3
Carefully open the vacuumpacked bag and sprinkle Geo-Fix
All Weather Jointing Compound
over the area to be jointed.



Step 4
Using a soft brush, push the
Geo-Fix All Weather Jointing
Compound into the joints at 45°
angle.



Firmly compact the Geo-Fix All Weather Jointing Compound with a pointing tool, refill and repeat ensuring a fully compacted and topped up joint.



Step 7
After application brush off excess with a soft brush, taking care not to brush out any Geo-Fix All Weather Jointing Compound from treated joints. Once cured, sit back and enjoy your new patio.



Finish the surface decoratively giving a smooth, flat finish with a pointing tool then move onto the next area. Firm compaction is the key to the successful laying of Geo-Fix All Weather Jointing Compound.

