

# SEALACRYL

## One Coat Acrylic Waterproofing Roof Coating



### WATERPROOFING SOLUTIONS RANGE

#### Description:

*A one component, UV stable, solvent-based, multi-purpose roof coating membrane. Designed to prevent the ingress of water whilst allowing any trapped moisture to escape and evaporate naturally. Manufactured with fibre reinforcement pre-dispersed in the can for ease of application.*

#### Benefits:

- ◆ Excellent adhesion.
- ◆ Application in damp weather.
- ◆ Instant protection.
- ◆ Superb solar reflectivity.
- ◆ Reinforced membrane.
- ◆ One coat application.
- ◆ Seamless.
- ◆ Fully flexible.
- ◆ Unaffected by temperature.
- ◆ Economical.

#### Uses

For renovation of all types of roof structure. Provides waterproof protection of: flat and pitched roofs, corrugated asbestos, roof lights, flashings, roofing felt, gutters, slate, asphalt, lead, glasshouses, metal and fibreglass. Will also bridge small gaps and cracks.

#### Preparation

All surfaces must be structurally sound, clean, dry and free from surface contaminants such as grease, rust and dirt. Clean metals with a wire brush to remove contamination and to provide a key. If necessary, remove any organic growth i.e. moss or lichen, with a fungicidal wash such as Bond It MOULD STOP. Make good all cracks, splits, small holes and flashings and ensure the area to be treated is free from standing water. SEALACRYL requires no primer on most surfaces and will tolerate damp surfaces although with any application for best results apply to a dry surface if possible. Carry out an adhesion test prior to application to determine if use of a primer is necessary.



#### Application

**Do not thin.** Apply SEALACRYL using either a brush or roller. Treat all details first, in areas where excessive movement may occur additional reinforcement can be incorporated into the coating. SEALACRYL can be applied in one coat, but experience has shown that a two coat application ensures a greater uniformity of coating thickness.

#### Drying Time

Normally 24 hours dependant on ambient temperature and ventilation.

#### Limitations

Not suitable for use on balconies and walkways. This product contains solvent and can attack certain materials, if in doubt please test before use.

#### Coverage

Average coverage is approximately 1-2Kg per square metre. Thick coatings may take up to a week to dry. The product may remain slightly soft for a period of time after application. This will not affect its waterproofing properties.

#### Cleaning Of Tools

Clean with Bond It WHITE SPIRIT.

#### Colours

Available in grey, white and black.

#### Storage Life

24 months from date of manufacture under good storage conditions in original unopened containers.

#### Storage Conditions

Store under cover away from sources of heat and ignition. Store between 5-20°C. Keep containers sealed when not in use.

#### Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

**Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.**

## Specification Summary

Type of Solvent	White Spirit/ pma
Approximate Specific Gravity	1.2
Approximate Coverage	Average coverage is approximately 1-2Kg per m <sup>2</sup>
Service Temperature Limits	-10°C to + 85°C depending on operating conditions
Application Temperature Limits	Normally 5°C to 25°C
Chemical Resistance	<b>Resistant to:</b> most salt solutions, dilute acids and alkalis. <b>Not resistant to:</b> oils, solvents, some detergent solutions and some glass cleaning compounds
UFI	4800-DORS-R005-D73J

### Product Details:

<b>Size:</b>	1Kg	5Kg	20Kg	2.5Kg
<b>Code:</b>	SA1GR	SA5GR	SA20GR	SA2P5GR
<b>Colour:</b>	Grey	Grey	Grey	Grey
<b>Barcode:</b>	5060021366078	5060021366061	5060021368348	5056437401083

<b>Size:</b>	1Kg	5Kg	20Kg
<b>Code:</b>	SA1WH	SA5WH	SA20WH
<b>Colour:</b>	White	White	White
<b>Barcode:</b>	5056437400338	5060021368461	5060021368485

<b>Size:</b>	1Kg	5Kg	20Kg
<b>Code:</b>	SA1BL	SA5BL	SA20BL
<b>Colour:</b>	Black	Black	Black
<b>Barcode:</b>	5056437400321	5060021368454	5060021368478



Part of the Bond It Roofing & Weatherproofing Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:  
6152  
ISO 9001; ISO 14001;  
ISO 45001



**BOND IT**  
Head Office: Unit G16 River Bank Way, Lowfields Business Park,  
Elland, West Yorkshire HX5 9DN.  
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310  
Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V4 01/03/17  
Supersedes: V3 12/01/16