

Construction Products Regulations (EU) 305 2011

DECLARATION OF PERFORMANCE

DOP - WP100

CE

1 Identification Code: WP100: Bond It WP100 Oxime Silicone
2. Batch Identification: By batch number – see print on packaging

3. Intended uses: F EXT-INT Façade Sealant for Exterior and Interior

Use. **G** Glazing Sealant. **XS2**.

4. Manufacturer: Seal It Services t/a Bond

It Unit G16 River Bank Way Lowfields Business

Park Elland

West Yorkshire, HX5 9DN

5. Authorised Representative: Not applicable6. System of assessment and System 3

Verification of constancy:

7. Notified Body: 0757

8. European Technical Assessment: Not Applicable

9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		EN 15651 1:2012
Resistance to Flow	≤3mm	Conditioning method
Loss of Volume	≤20%	B. Tested on Mortar
Tensile properties at maintained extension	Pass	M1 without primer.
Tensile Properties – secant modulus	Pass	EN15651-3:2012 Conditioning method B. Tested on Aluminium without primer.
Adhesion/cohesion at variable temperature	Pass	
Adhesion/cohesion after water immersion.	Pass	
Adhesion/cohesion after exposure to heat, water and artificial light	Pass	
Elastic Recovery	>40%	
Durability	Pass	
Microbiological growth	2	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

Aoxley

Regulatory & Technical Data Manager

Issue 5: 16th March 2022

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 <u>www.bonditgroup.com</u>



Construction Products Regulations (EU) 305 2011

DECLARATION OF PERFORMANCE

DOP - WP100



1 Identification Code: WP100 : Bond It WP100 Oxime Silicone
2. Batch Identification: By batch number – see print on packaging

3. Intended uses: F EXT-INT Façade Sealant for Exterior and Interior

Use. **G** Glazing Sealant. **XS2**. Seal It Services t/a Bond It Unit G16 River Bank Way Lowfields Business

Park Elland

West Yorkshire, HX5 9DN

5. Authorised Representative: Not applicable6. System of assessment and System 3

Verification of constancy:

4. Manufacturer:

7. Notified Body: 0757

8. European Technical Assessment: Not Applicable

9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		EN 15651 1:2012
Resistance to Flow	≤3mm	Conditioning method
Loss of Volume	≤20%	B. Tested on Mortar
Tensile properties at maintained	Pass	M1 without primer.
extension		·
Tensile Properties – secant	Pass	EN15651-3:2012
modulus		Conditioning method
Adhesion/cohesion at variable	Pass	B. Tested on
temperature		Aluminium without
Adhesion/cohesion after	Pass	
water immersion.		primer.
Adhesion/cohesion after	Pass	
exposure to heat, water		
and artificial light		
Elastic Recovery	>40%	
Durability	Pass	
Microbiological growth	2	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

Aoxley

Amy Oxley Regulatory & Technical Data Manager

Issue 1: 20th October 2022

Seal It Services Ltd T/As Bond It: Tel: 01422 315300 www.bonditgroup.com