according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DOWSIL™ 995 Silicone Structural Sealant Black

Product code : 02369052

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Adhesive, binding agents

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : DOW CHEMICAL COMPANY LIMITED

STATION ROAD, BIRCH VALE, HIGH PEAK

DERBYSHIRE England SK22 1BR

UNITED KINGDOM

Telephone : +44 (0) 1663 746518

Telefax : +44 (0) 1663 746605

E-mail address of person

responsible for the SDS

: SDSQuestion@dow.com

1.4 Emergency telephone number

24-Hour Emergency Contact : 0031 115 694 982

Local Emergency Contact : 00 31 115 69 4982

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Precautionary statements : Prevention:

P271 Use only outdoors or in a well-ventilated area.

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains Methyltrimethoxysilane, 3-Mercaptopropyl trimethoxysilane. May pro-

duce an allergic reaction.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Silicone elastomer

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
Methyltrimethoxysilane	1185-55-3	Flam. Liq. 2; H225	>= 0.1 - < 1
	214-685-0	Skin Sens. 1B; H317	
	01-2119517436-40		
3-Mercaptopropyl trimethoxysi-	4420-74-0	Acute Tox. 4; H302	>= 0.1 - < 0.25
lane	224-588-5	Skin Sens. 1B; H317	
		Aquatic Chronic 2;	
		H411	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders : No special precautions are necessary for first aid responders.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May produce an allergic reaction.

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides Silicon oxides Formaldehyde Metal oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if ne-

cessary. Use personal protective equipment.

Specific extinguishing me-

thods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice and personal protective equip-

ment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in properly labelled containers. Store in accordance with

the particular national regulations.

Advice on common storage : Do not store with the following product types:

Strong oxidizing agents

7.3 Specific end use(s)

Specific use(s) : These precautions are for room temperature handling. Use at

elevated temperature or aerosol/spray applications may re-

quire added precautions.

according to Regulation (EC) No. 1907/2006



Basis

DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

Value type (Form

Control parameters

SECTION 8: Exposure controls/personal protection

CAS-No.

8.1 Control parameters

Components

Occupational Exposure Limits

		of exposure)		
Calcium carbonate treated with stearic acid	Not As- signed	TWA (inhalable dust)	10 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
		TWA (Respirable dust)	4 mg/m3	GB EH40
Further information	fractions of air in accordance sampling and COSHH definition kind when pre 8-hour TWA of This means the above these leposure to the contain particul of any particul body response HSE distinguis 'inhalable' and	ses of these limits, reborne dust which wi with the methods degravimetric analysistion of a substance sent at a concentrate inhalable dust or 4 at any dust will be sevels. Some dusts he must comply with es of a wide range of a reparticle after entry of that it elicits, dependent of the server of	espirable dust and inhalable of the collected when sampling escribed in MDHS14/3 Gene of respirable and inhalable of hazardous to health includes ion in air equal to or greater to mg.m-3 8-hour TWA of respubject to COSHH if people at ave been assigned specific Variety the appropriate limit., Most in finite sizes. The behaviour, depoy into the human respiratory and on the nature and size of the for limit-setting purposes to ble dust approximates to the e and mouth during breathing	g is undertaken ral methods for dust, The dust of any than 10 mg.m-3 irable dust. The exposed VELs and exndustrial dusts sition and fate system and the the particle.

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

	fore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
Methyltrimethox- ysilane	1185-55-3	TWA	7.5 ppm	DCC OEL

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Calcium carbonate treated with stearic acid

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Methyltrimethoxysi- lane	Workers	Skin contact	Acute systemic ef- fects	0.38 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	25.6 mg/m3
	Workers	Skin contact	Long-term systemic effects	0.38 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	25.6 mg/m3
	Consumers	Skin contact	Acute systemic effects	0.3 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	6.25 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0.26 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	0.3 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	6.25 mg/m3
	Consumers	Ingestion	Acute systemic effects	0.26 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Methyltrimethoxysilane	Fresh water	>= 1.3 mg/l
	Marine water	>= 0.13 mg/l
	Fresh water sediment	>= 1.1 mg/kg
	Marine sediment	>= 0.11 mg/kg
	Soil	>= 0.17 mg/kg
	Sewage treatment plant	> 6.9 mg/l

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10). Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

William 20 Workplade expedent concentre

Personal protective equipment

Eye protection : Wear the following personal protective equipment:

Safety glasses

Hand protection

Remarks : For prolonged or repeated contact use protective gloves.

Wash hands before breaks and at the end of workday.

Skin and body protection : Skin should be washed after contact.

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : paste

Colour : black

Odour : alcohol-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Initial boiling point and boiling

range

Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : Not applicable

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

Relative vapour density : No data available

Relative density : 1.33

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weight : No data available

Particle size : No data available

Self-ignition : The substance or mixture is not classified as pyrophoric. The

substance or mixture is not classified as self heating.

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Use at elevated temperatures may form highly hazardous

compounds.

Can react with strong oxidizing agents.

Methyl alcohol is formed upon contact with water or humid air. Hazardous decomposition products will be formed at elevated

temperatures.

10.4 Conditions to avoid

Conditions to avoid : None known.

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

Thermal decomposition : Formaldehyde

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of $\,:\,\,$ Skin contact

exposure Ingestion

Eye contact

Acute toxicity

Not classified based on available information.

Components:

Methyltrimethoxysilane:

Acute oral toxicity : LD50 (Rat): 12.3 ml/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Information taken from reference works and the

literature.

Acute inhalation toxicity : LC50 (Rat): > 42.1 mg/l

Exposure time: 6 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: On basis of test data.

Acute dermal toxicity : LD50 (Rabbit): > 9,500 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: On basis of test data.

3-Mercaptopropyl trimethoxysilane:

Acute oral toxicity : LD50 (Rat): 0.73 ml/kg

Remarks: On basis of test data.

Acute dermal toxicity : LD50 (Rat): 2.14 ml/kg

Remarks: On basis of test data.

Skin corrosion/irritation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

Components:

Methyltrimethoxysilane:

Species: Rabbit

Result: No skin irritation

Remarks: On basis of test data.

3-Mercaptopropyl trimethoxysilane:

Species: Rabbit

Result: No skin irritation

Remarks: On basis of test data.

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Methyltrimethoxysilane:

Species: Rabbit

Result: No eye irritation

Remarks: On basis of test data.

3-Mercaptopropyl trimethoxysilane:

Species: Rabbit

Result: No eye irritation

Remarks: On basis of test data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Methyltrimethoxysilane:

Assessment: Probability or evidence of low to moderate skin sensitisation rate in humans

Test Type: Buehler Test Species: Guinea pig Result: positive

Remarks: On basis of test data.

3-Mercaptopropyl trimethoxysilane:

Assessment: Probability or evidence of low to moderate skin sensitisation rate in humans

Test Type: Buehler Test

Remarks: On basis of test data.

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

Germ cell mutagenicity

Not classified based on available information.

Components:

Methyltrimethoxysilane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: On basis of test data.

Test Type: Mutagenicity (in vitro mammalian cytogenetic test)

Result: positive

Remarks: On basis of test data.

Test Type: Chromosome aberration test in vitro

Result: positive

Remarks: On basis of test data.

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: negative

Remarks: On basis of test data.

Germ cell mutagenicity- As-

sessment

Animal testing did not show any mutagenic effects.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

Methyltrimethoxysilane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: Ingestion Symptoms: No effects on fertility Remarks: On basis of test data.

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: Ingestion

Symptoms: No effects on foetal development

Remarks: On basis of test data.

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

Reproductive toxicity - As-

sessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

Methyltrimethoxysilane:

Exposure routes: inhalation (vapour)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or

less.

Exposure routes: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg

bw or less.

Repeated dose toxicity

Components:

Methyltrimethoxysilane:

Species: Rat

Application Route: inhalation (vapour) Remarks: On basis of test data.

Species: Rat

Application Route: Ingestion Remarks: On basis of test data.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Methyltrimethoxysilane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 110 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia sp. (water flea)): > 122 mg/l

Exposure time: 48 h

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 120

mg/l

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

Version Revision Date: SDS Number: Date of last issue: 10.03.2017 1.11 04.03.2018 935436-00012 Date of first issue: 11.12.2014

Exposure time: 72 h

Method: OECD Test Guideline 201

EC50 : > 100 mg/lToxicity to microorganisms

Method: OECD Test Guideline 209

3-Mercaptopropyl trimethoxysilane:

Toxicity to fish LC50 (Danio rerio (zebra fish)): 439 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 6.7 mg/l

Exposure time: 48 h

Toxicity to algae : ErC50 (Scenedesmus subspicatus): 931 mg/l

Exposure time: 72 h

Toxicity to microorganisms EC50: 440 mg/l

Ecotoxicology Assessment

Chronic aquatic toxicity Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

3-Mercaptopropyl trimethoxysilane:

Biodegradability Result: Not readily biodegradable.

> Biodegradation: 51 % Exposure time: 28 d

Method: OECD Test Guideline 301

12.3 Bioaccumulative potential

Components:

Methyltrimethoxysilane:

Partition coefficient: n-

octanol/water

: log Pow: -2.36

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High

: Not applicable

Concern for Authorisation (Article 59).

Regulation (EC) No 1005/2009 on substances that dep-

lete the ozone layer

Not applicable

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

Not applicable

Regulation (EC) No 649/2012 of the European Parlia-

: Not applicable

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

ment and the Council concerning the export and import of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

The components of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from

inventory listing.

PICCS : All ingredients listed or exempt.

REACH : For purchases from Dow Chemical EU legal entities, all ingre-

dients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Chemical legal entities with the intention to export into EEA please contact your DC repre-

sentative/local office.

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

KECI : One or more ingredients are not listed or exempt.

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the Ca-

nadian Domestic Substances List (DSL).

TCSI : All ingredients listed or exempt.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.

H302 : Harmful if swallowed.

H317 : May cause an allergic skin reaction.

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

Acute Tox. : Acute toxicity

Aquatic Chronic : Chronic aquatic toxicity
Flam. Liq. : Flammable liquids
Skin Sens. : Skin sensitisation
DCC OEL : Dow Chemical Guide

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

DCC OEL / TWA : Time weighted average

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

according to Regulation (EC) No. 1907/2006



DOWSIL™ 995 Silicone Structural Sealant Black

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10.03.2017

 1.11
 04.03.2018
 935436-00012
 Date of first issue: 11.12.2014

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN