

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD 565 CLEAN ROOM SILICONE

Revision Date 03.01.2020

Version 3.0

Print Date 03.01.2020



BUILDING TRUST



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : EVERBUILD 565 CLEAN ROOM SILICONE

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company : Everbuild – A Sika Company  
Site 41  
Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds  
West Yorkshire LS9 0SW  
United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

#### 1.4 Emergency telephone number

Emergency telephone number : 0044 113 240 3456 (office hours only)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.  
H412 Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD 565 CLEAN ROOM SILICONE

Revision Date 03.01.2020



BUILDING TRUST



Version 3.0

Print Date 03.01.2020

fects.

Precautionary statements :

### Prevention:

P264 Wash skin thoroughly after handling.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.

### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.

### Disposal:

P501 Dispose of contents/container in accordance with local regulation.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

| Chemical name                                                                                                | CAS-No.<br>EC-No.<br>Registration number         | Classification                                                                                                | Concentration<br>(% w/w) |
|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------|--------------------------|
| trimethoxyvinylsilane<br>Contains:<br>tetramethyl orthosilicate <= 0,2 %                                     | 2768-02-7<br>220-449-8<br>01-2119513215-52-XXXX  | Flam. Liq. 3; H226<br>Acute Tox. 4; H332                                                                      | >= 1 - < 2,5             |
| bis(ethyl acetoacetato-O1',O3)bis(2-methylpropan-1-olato)titanium<br>Contains:<br>2-methylpropan-1-ol <= 2 % | 83877-91-2<br>281-161-6<br>01-2119968551-31-XXXX | Flam. Liq. 3; H226<br>Skin Irrit. 2; H315<br>Eye Dam. 1; H318<br>STOT SE 3; H335<br>STOT SE 3; H336           | >= 1 - < 2,5             |
| p-[(diiodomethyl)sulphonyl]toluene                                                                           | 20018-09-1<br>243-468-3                          | Acute Tox. 3; H331<br>Eye Dam. 1; H318<br>STOT RE 2; H373<br>Aquatic Acute 1; H400<br>Aquatic Chronic 1; H410 | >= 0,25 - < 1            |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD 565 CLEAN ROOM SILICONE

Revision Date 03.01.2020

Version 3.0

Print Date 03.01.2020



BUILDING TRUST



|          |                                               |                                                                                                                            |     |
|----------|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|-----|
| methanol | 67-56-1<br>200-659-6<br>01-2119433307-44-XXXX | STOT SE 1; H370<br>Flam. Liq. 2; H225<br>Acute Tox. 3; H301<br>Acute Tox. 3; H331<br>Acute Tox. 3; H311<br>STOT SE 1; H370 | < 1 |
|----------|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|-----|

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Excessive lachrymation  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
Causes serious eye irritation.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD 565 CLEAN ROOM SILICONE

Revision Date 03.01.2020

Version 3.0

Print Date 03.01.2020



BUILDING TRUST



### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD 565 CLEAN ROOM SILICONE

Revision Date 03.01.2020

Version 3.0

Print Date 03.01.2020



BUILDING TRUST



### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep container tightly closed in a dry and well-ventilated areas and containers place. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components | CAS-No.                                                                                                                                                                      | Value type (Form of exposure) | Control parameters * | Basis *    |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|----------------------|------------|
| methanol   | 67-56-1                                                                                                                                                                      | TWA                           | 200 ppm<br>260 mg/m3 | 2006/15/EC |
|            | Further information: Indicative, Identifies the possibility of significant uptake through the skin                                                                           |                               |                      |            |
|            |                                                                                                                                                                              | TWA                           | 200 ppm<br>266 mg/m3 | GB EH40    |
|            | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                               |                      |            |
|            |                                                                                                                                                                              | STEL                          | 250 ppm<br>333 mg/m3 | GB EH40    |

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### Occupational exposure limits of decomposition products

| Components | CAS-No.                                                                                                                                                                      | Value type (Form of exposure) | Control parameters * | Basis *    |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|----------------------|------------|
| methanol   | 67-56-1                                                                                                                                                                      | TWA                           | 200 ppm<br>260 mg/m3 | 2006/15/EC |
|            | Further information: Indicative, Identifies the possibility of significant uptake through the skin                                                                           |                               |                      |            |
|            |                                                                                                                                                                              | TWA                           | 200 ppm<br>266 mg/m3 | GB EH40    |
|            | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                               |                      |            |
|            |                                                                                                                                                                              | STEL                          | 250 ppm<br>333 mg/m3 | GB EH40    |

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use            | Exposure routes | Potential health effects | Value    |
|----------------|--------------------|-----------------|--------------------------|----------|
| methanol       | Workers            | Skin contact    |                          | 40 mg/m3 |
| Remarks:       | Exposure time: 8 h |                 |                          |          |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD 565 CLEAN ROOM SILICONE

Revision Date 03.01.2020

Version 3.0

Print Date 03.01.2020



BUILDING TRUST



|          |                    |              |           |
|----------|--------------------|--------------|-----------|
|          | Consumers          | Skin contact | 260 mg/m3 |
| Remarks: | Exposure time: 8 h |              |           |

### 8.2 Exposure controls

#### Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (0,4 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : paste
- Colour : white
- Odour : sweet
- Odour Threshold : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD 565 CLEAN ROOM SILICONE

Revision Date 03.01.2020

Version 3.0



BUILDING TRUST



Print Date 03.01.2020

|                                                  |   |                                   |
|--------------------------------------------------|---|-----------------------------------|
| pH                                               | : | Not applicable                    |
| Melting point/range / Freezing point             | : | No data available                 |
| Boiling point/boiling range                      | : | No data available                 |
| Flash point                                      | : | Not applicable                    |
| Evaporation rate                                 | : | No data available                 |
| Flammability (solid, gas)                        | : | No data available                 |
| Upper explosion limit / Upper flammability limit | : | No data available                 |
| Lower explosion limit / Lower flammability limit | : | No data available                 |
| Vapour pressure                                  | : | 0,01 hPa                          |
| Relative vapour density                          | : | No data available                 |
| Density                                          | : | ca. 1,4 g/cm <sup>3</sup> (20 °C) |
| Solubility(ies)                                  |   |                                   |
| Water solubility                                 | : | insoluble                         |
| Solubility in other solvents                     | : | No data available                 |
| Partition coefficient: n-octanol/water           | : | No data available                 |
| Auto-ignition temperature                        | : | No data available                 |
| Decomposition temperature                        | : | No data available                 |
| Viscosity                                        |   |                                   |
| Viscosity, dynamic                               | : | No data available                 |
| Viscosity, kinematic                             | : | > 20,5 mm <sup>2</sup> /s (40 °C) |
| Explosive properties                             | : | No data available                 |
| Oxidizing properties                             | : | No data available                 |

### 9.2 Other information

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD 565 CLEAN ROOM SILICONE

Revision Date 03.01.2020

Version 3.0

Print Date 03.01.2020



BUILDING TRUST



### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

#### 10.4 Conditions to avoid

Conditions to avoid : No data available

#### 10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

Hazardous decomposition products : methanol

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Not classified based on available information.

##### Components:

##### **trimethoxyvinylsilane:**

Acute oral toxicity : LD50 Oral (Rat): ca. 7.120 mg/kg

Acute inhalation toxicity : LC50: ca. 16,8 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50: 3.540 mg/kg

##### **methanol:**

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Converted acute toxicity point estimate

##### **Skin corrosion/irritation**

Not classified based on available information.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD 565 CLEAN ROOM SILICONE

Revision Date 03.01.2020

Version 3.0

Print Date 03.01.2020



BUILDING TRUST



### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD 565 CLEAN ROOM SILICONE

Revision Date 03.01.2020

Version 3.0

Print Date 03.01.2020



BUILDING TRUST



Harmful to aquatic life with long lasting effects.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

### SECTION 14: Transport information

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD 565 CLEAN ROOM SILICONE

Revision Date 03.01.2020

Version 3.0

Print Date 03.01.2020



BUILDING TRUST



REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : None of the components are listed ( $\Rightarrow$  0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 0,2 %  
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 0,2 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H301 : Toxic if swallowed.  
H311 : Toxic in contact with skin.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD 565 CLEAN ROOM SILICONE

Revision Date 03.01.2020

Version 3.0

Print Date 03.01.2020



BUILDING TRUST



|      |                                                                      |
|------|----------------------------------------------------------------------|
| H315 | : Causes skin irritation.                                            |
| H318 | : Causes serious eye damage.                                         |
| H331 | : Toxic if inhaled.                                                  |
| H332 | : Harmful if inhaled.                                                |
| H335 | : May cause respiratory irritation.                                  |
| H336 | : May cause drowsiness or dizziness.                                 |
| H370 | : Causes damage to organs.                                           |
| H373 | : May cause damage to organs through prolonged or repeated exposure. |
| H400 | : Very toxic to aquatic life.                                        |
| H410 | : Very toxic to aquatic life with long lasting effects.              |

### Full text of other abbreviations

|                  |                                                                                                                                                                                                                                        |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acute Tox.       | : Acute toxicity                                                                                                                                                                                                                       |
| Aquatic Acute    | : Short-term (acute) aquatic hazard                                                                                                                                                                                                    |
| Aquatic Chronic  | : Long-term (chronic) aquatic hazard                                                                                                                                                                                                   |
| Eye Dam.         | : Serious eye damage                                                                                                                                                                                                                   |
| Flam. Liq.       | : Flammable liquids                                                                                                                                                                                                                    |
| Skin Irrit.      | : Skin irritation                                                                                                                                                                                                                      |
| STOT RE          | : Specific target organ toxicity - repeated exposure                                                                                                                                                                                   |
| STOT SE          | : Specific target organ toxicity - single exposure                                                                                                                                                                                     |
| 2006/15/EC       | : Europe. Indicative occupational exposure limit values                                                                                                                                                                                |
| GB EH40          | : UK. EH40 WEL - Workplace Exposure Limits                                                                                                                                                                                             |
| 2006/15/EC / TWA | : Limit Value - eight hours                                                                                                                                                                                                            |
| GB EH40 / TWA    | : Long-term exposure limit (8-hour TWA reference period)                                                                                                                                                                               |
| GB EH40 / STEL   | : Short-term exposure limit (15-minute reference period)                                                                                                                                                                               |
| ADR              | : European Agreement concerning the International Carriage of Dangerous Goods by Road                                                                                                                                                  |
| CAS              | : Chemical Abstracts Service                                                                                                                                                                                                           |
| DNEL             | : Derived no-effect level                                                                                                                                                                                                              |
| EC50             | : Half maximal effective concentration                                                                                                                                                                                                 |
| GHS              | : Globally Harmonized System                                                                                                                                                                                                           |
| IATA             | : International Air Transport Association                                                                                                                                                                                              |
| IMDG             | : International Maritime Code for Dangerous Goods                                                                                                                                                                                      |
| LD50             | : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)                                                                                                |
| LC50             | : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)                                                                                                 |
| MARPOL           | : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978                                                                                                                        |
| OEL              | : Occupational Exposure Limit                                                                                                                                                                                                          |
| PBT              | : Persistent, bioaccumulative and toxic                                                                                                                                                                                                |
| PNEC             | : Predicted no effect concentration                                                                                                                                                                                                    |
| REACH            | : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC             | : Substances of Very High Concern                                                                                                                                                                                                      |
| vPvB             | : Very persistent and very bioaccumulative                                                                                                                                                                                             |

### Further information

Classification of the mixture:

Classification procedure:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## EVERBUILD 565 CLEAN ROOM SILICONE

Revision Date 03.01.2020

Version 3.0

Print Date 03.01.2020



BUILDING TRUST



Eye Irrit. 2

H319

Calculation method

Aquatic Chronic 3

H412

Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

GB / EN