

EVERBUILD FIREMATE

DECLARATION OF PERFORMANCE

No. 94212807

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	FIRE / FIREMATE		
2	INTENDED USE/S	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements		
3	MANUFACTURER:	Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Industrial Estate, Leeds, UK, LS9 OSW		
4	AUTHORISED REPRESENTATIVE:	Not applicable		
5	SYSTEM/S OF AVCP:	4 The Allerton Allerton and the control of the cont		
6a	HARMONISED STANDARD:	EN15651-1:2012		
	Notified body/ies:	Not applicable		

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Release of dangerous chemicals	See sds		
Reaction to fire	Class E	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Resistance to flow	≤5mm		
Loss of volume	≤ 45%		
Tensile properties (i.e. elongation): - break at 23°C	≥ 25%		EN15651- 1:2012
	- V	1	
ATTION OF THE DESIGNATION OF THE OWNER, THE			

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Paul Thomas

Function: Technical Product

Coordinator

At Leeds on 09 October 2019

Name: Andrew Stockill

Function: QA / QC Supervisor At Leeds on 09 October 2019

End of information as required by Regulation (EU) No 305/2011

Add Related DoP

Declaration of Performance FIRE / FIREMATE 94212807 2019.10 , ver. 02 1213 Template for translation. Only for internal use DISTRIBUTION





Everbuild Building Products LTD, Leeds, UK

DoP No. 94212807

EN15651-1:2012

Notified Body Not applicable

Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements

Release of dangerous chemicals	See sds			
Reaction to fire	Class E	4	17.19	
Resistance to flow	≤ 5mm			
Loss of volume	≤ 45%			
Tensile properties (i.e. elongation): - break at 23°C	≥ 25%			
			TREE	
			378	
			7 1 1 1	
			ENFAIRE IN	

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance FIRE / FIREMATE 94212807 2019.10 , ver. 02 1213

Template for translation. Only for internal use DISTRIBUTION



