



## **Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,
Cross Green Industrial Estate, Leeds, LS9 0SW
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

## CONSTRUCTION PRODUCTS REGULATION DECLARATION OF PERFORMANCE

No: 700TTR/2-CPR/2014

Substrate: Anodised aluminium and Mortar M1

Primer: No primer

| 1. Identification Code                      | EVERFLEX Silicone 700T Trans   |
|---|--|
|   | Codes: 700TTR / FP700TTR   |
| 2. Type, Batch and/or Serial Number         | - For batch number - see packaging   |
| 3. Intended use                             | Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements |
| 4. Manufacturer                             | Everbuild Building Products ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW           |
| 5. Authorised Representative                | Not Applicable   |
| 6. Assessment and Verification of Constancy | System 3   |
| of Performance                              |  |
| 7. Notified Body and Tasks                  | GINGER CEBTP Notified Body No. 0074  |
| 8. European Technical Assessment            | Not Applicable   |
| 9. Declared Performance                     | TO EN15651-1 (2012)  |
| Туре  | F EXT-INT CC   |
| Classification                              | F12.5E   |
| Reaction to Fire                            | Class E  |



## **Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,
Cross Green Industrial Estate, Leeds, LS9 0SW
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

|   | Website. WWW.everballa.co.ak |
|---|------------------------------|
| Loss of Volume ISO10563   | ≤25%                         |
| Resistance to flow ISO7390  | ≤3 mm                        |
| Adhesion / cohesion properties (-30°C) ISO 8339 modified                                    | ≤ 0.9 MPa                    |
| Adhesion / cohesion properties at maintained extension (-30°C) ISO 8340 modified            | NF                           |
| Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590 | NF                           |
| Durability ISO 8340, ISO 9047 and ISO 10590   | Pass                         |

Substrate: Anodised aluminium

Primer: No primer

| 1. Identification Code                      | EVERFLEX Silicone 700T Trans                          |
|---|---|
|   | Codes: 700TTR / FP700TTR                              |
| 2. Type, Batch and/or Serial Number         | - For batch number - see packaging                    |
| 3. Intended use                             | Sealant for non-structural use in joints in buildings |
|   | and pedestrian walkways Part 3: Sealants for          |
|   | Sanitary elements                                     |
| 4. Manufacturer                             | Everbuild Building Products ltd, Site 41, Cross Green |
|   | Industrial Estate, Knowsthorpe Way, Leeds, LS9 OSW    |
| 5. Authorised Representative                | Not Applicable  |
| 6. Assessment and Verification of Constancy | System 3  |
| of Performance                              |   |
| 7. Notified Body and Tasks                  | Ginger CEBTP Notified Body No. 00074                  |
| 8. European Technical Assessment            | Not Applicable  |



## **Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,
Cross Green Industrial Estate, Leeds, LS9 0SW
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk

|   | website: www.everbuild.co.uk |
|---|------------------------------|
| 9. Declared Performance   | TO EN15651-3 (2012)          |
| Туре  | S                            |
| Classification  | XS2                          |
| Reaction to Fire  | Class E                      |
| Loss of Volume ISO10563   | ≤20%                         |
| Resistance to flow ISO7390  | ≤3 mm                        |
| Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590 | NF                           |
| Action of the microorganisms : Intensity of growth ISO 846, method B                        | 2                            |
| Durability ISO 846, method B, ISO 8340, ISO 9047 and ISO 10590                              | Pass                         |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington – Head of Technical

P.R. Thomas – Technical Manager

Dated: Leeds, 30/6/14