



Site 41, Knowsthorpe Way, Cross Green Industrial Estate, Leeds, LS9 0SW Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424 Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

CONSTRUCTION PRODUCTS REGULATION

DECLARATION OF PERFORMANCE

No: HYB480/1-CPR/ 2014

Substrate: Anodised aluminium and Mortar M1

Primer: No primer on Aluminium, Sikaflex Primer 3-N for Mortar

Everbuild TECNIC HYRIFLEX 480
Codes: HYB480
- For batch number - see packaging
Sealant for non-structural use in joints in buildings
and pedestrian walkways Part 1: Sealants for Façade
elements
Everbuild Building Products ltd, Site 41, Cross Green
Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW
Not Applicable
System 3
SKZ Notified Body No. 1213
Not Applicable
TO EN15651-1 (2012)
F EXT-INT-CC
F25HM



Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

Reaction to Fire	Class E
Loss of Volume ISO10563	≤10%
	210/0
Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	NF
Adhesion/cohesion properties ISO 8340 modified (-30°C)	NF
Durability ISO 8340, ISO 9047 and ISO 10590	Pass

Substrate: Anodised aluminium and Mortar M1

Primer: No primer on Aluminium, Sikaflex Primer 3-N for Mortar

1. Identification Code	Everbuild TECNIC HYRIFLEX 480
	Codes: HYB480
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 3: Sealants for Sanitary elements
4. Manufacturer	Everbuild Building Products ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 OSW
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy of Performance	System 3



Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

7. Notified Body and Tasks	SKZ Notified Body No. 1213	
8. European Technical Assessment	Not Applicable	
9. Declared Performance TO EN15651-4 (2012)		
Туре	PW EXT-INT-CC	
Classification	PW25HM	
Reaction to Fire	Class E	
Loss of Volume ISO10563	≤10%	
Resistance to flow ISO7390	≤3 mm	
Adhesion/cohesion properties at maintained extension (23°C) ISO 8340	NF	
Tear Resistance ISO 8340 modified	NF	
Adhesion / Cohesion properties at maintained extension 28 days water immersion (23°C) ISO 10590 modified	NF change of secant modulus: ≤50%	
Adhesion / Cohesion properties at maintained extension 28 days salt water immersion (23°C)) ISO 10590 modified	NF	
Adhesion/cohesion properties at maintained extension (-30°C) ISO 8340 modified	NF	
Durability ISO 8340, ISO 9047 and ISO 10590	Pass	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



Site 41, Knowsthorpe Way, Cross Green Industrial Estate, Leeds, LS9 0SW Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424 Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

Signed: I. G. Southerington – Head of Technical

P.R. Thomas – Technical Manager

- Julle

Dated: Leeds, 12/6/14