according to Regulation (EC) No. 1907/2006

# **Everbuild Technic Hybriflex SMP**



BUILDING TRUST

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Everbuild Technic Hybriflex SMP

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

### 1.3 Details of the supplier of the safety data sheet

Company : Everbuild – A Sika Company

Site 41

Knowsthorpe Way

Cross Green Industrial Estate

Leeds

West Yorkshire LS9 0SW

United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

# 1.4 Emergency telephone number

Emergency telephone num-

ber

: 0044 113 240 3456 (office hours only)

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat-

H412: Harmful to aquatic life with long lasting ef-

egory 3 fe

fects.

### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting ef-

according to Regulation (EC) No. 1907/2006

# **Everbuild Technic Hybriflex SMP**







fects.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P273 Avoid release to the environment.

Wear protective gloves.

Disposal:

P280

P501 Dispose of contents/container in accordance

with local regulation.

Hazardous components which must be listed on the label:

Pentamethyl piperidylsebacate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

### Components

| Chemical name                      | CAS-No.             | Classification      | Concentration |
|------------------------------------|---------------------|---------------------|---------------|
|                                    | EC-No.              |                     | (% w/w)       |
|                                    | Registration number |                     |               |
| trimethoxyvinylsilane              | 2768-02-7           | Flam. Liq. 3; H226  | >= 1 - < 2,5  |
| Contains:                          | 220-449-8           | Acute Tox. 4; H332  |               |
| tetramethyl orthosilicate <= 0,2 % | 01-2119513215-52-   |                     |               |
|                                    | XXXX                |                     |               |
| Pentamethyl piperidylsebacate      | 1065336-91-5        | Skin Sens. 1A; H317 | >= 0,25 - < 1 |
| Contains:                          | 915-687-0           | Aquatic Acute 1;    |               |
| bis(1,2,2,6,6-pentamethyl-4-       | 01-2119491304-40-   | H400                |               |
| piperidyl) sebacate                | XXXX                | Aquatic Chronic 1;  |               |
| methyl 1,2,2,6,6-pentamethyl-4-    |                     | H410                |               |
| piperidyl sebacate                 |                     |                     |               |

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

according to Regulation (EC) No. 1907/2006

# **Everbuild Technic Hybriflex SMP**



If inhaled Move to fresh air.

Consult a physician after significant exposure.

BUILDING TRUST

In case of skin contact Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Do not induce vomiting without medical advice. If swallowed

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** Allergic reactions

See Section 11 for more detailed information on health effects

and symptoms.

Risks : sensitising effects

May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

**SECTION 5: Firefighting measures** 

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for firefighters

Further information : Standard procedure for chemical fires.

**SECTION 6: Accidental release measures** 

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Country GB 100000017291

3 / 12

according to Regulation (EC) No. 1907/2006

## **Everbuild Technic Hybriflex SMP**





Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

: No decomposition if stored and applied as directed.


### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

Country GB 100000017291

according to Regulation (EC) No. 1907/2006

# **Everbuild Technic Hybriflex SMP**







Print Date 03.01.2020

use.

## **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

Contains no substances with occupational exposure limit values.

### Occupational exposure limits of decomposition products

| Components | CAS-No.       | Value type (Form of exposure)                                                                                                                                                | Control parame-<br>ters * | Basis *    |  |  |
|------------|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|------------|--|--|
| methanol   | 67-56-1       | TWA                                                                                                                                                                          | 200 ppm<br>260 mg/m3      | 2006/15/EC |  |  |
|            |               | Further information: Indicative, Identifies the possibility of significant uptake through the skin                                                                           |                           |            |  |  |
|            | ,             | TWA                                                                                                                                                                          | 200 ppm<br>266 mg/m3      | GB EH40    |  |  |
|            | signed substa | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                           |            |  |  |
|            |               | STEL                                                                                                                                                                         | 250 ppm<br>333 mg/m3      | GB EH40    |  |  |

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

## Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

### **Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

according to Regulation (EC) No. 1907/2006

## **Everbuild Technic Hybriflex SMP**







Print Date 03.01.2020

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Appearance : paste

Colour grey

Odour : alcohol-like

Odour Threshold : No data available

pΗ Not applicable

Melting point/range / Freezing : No data available

Boiling point/boiling range : No data available

> 61 °C Flash point

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : 0,01 hPa

Relative vapour density : No data available

Density : ca. 1,4 g/cm3 (20 °C)

Solubility(ies)

Water solubility insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic 120.000 - 300.000 mPa.s (15 - 20 °C)

 $> 20,5 \text{ mm2/s} (40 ^{\circ}\text{C})$ Viscosity, kinematic

Explosive properties

according to Regulation (EC) No. 1907/2006

# **Everbuild Technic Hybriflex SMP**



: No data available



Print Date 03.01.2020

Oxidizing properties : No data available

### 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

## 10.6 Hazardous decomposition products

Hazardous decomposition

products

: methanol

# **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

# **Acute toxicity**

Not classified based on available information.

### Components:

# trimethoxyvinylsilane:

Acute oral toxicity : LD50 Oral (Rat): ca. 7.120 mg/kg

Acute inhalation toxicity : LC50: ca. 16,8 mg/l Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50: 3.540 mg/kg

# Pentamethyl piperidylsebacate:

according to Regulation (EC) No. 1907/2006

# **Everbuild Technic Hybriflex SMP**





Print Date 03.01.2020

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

## Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitisation

### Skin sensitisation

May cause an allergic skin reaction.

### Respiratory sensitisation

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

# STOT - single exposure

Not classified based on available information.

## STOT - repeated exposure

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

### **Components:**

Pentamethyl piperidylsebacate:

Toxicity to fish : LC50 (Fish): 0,97 mg/l

Exposure time: 96 h

M-Factor (Acute aquatic tox- : 1

icity)

M-Factor (Chronic aquatic

toxicity)

: 1

### 12.2 Persistence and degradability

No data available

# 12.3 Bioaccumulative potential

No data available

according to Regulation (EC) No. 1907/2006

## **Everbuild Technic Hybriflex SMP**





No data available

### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

## 12.6 Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

## **SECTION 14: Transport information**

### 14.1 UN number

Not regulated as a dangerous good

# 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

## 14.4 Packing group

Not regulated as a dangerous good

Country GB 100000017291

Print Date 03.01.202

9 / 12



according to Regulation (EC) No. 1907/2006

# **Everbuild Technic Hybriflex SMP**

Revision Date 03.01.2020 Version 2.0





Print Date 03.01.2020



### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 3

1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich (Number on list 52)

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

All substances contained in our Products are **REACH Information:** 

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds Law on the incentive tax for volatile organic compounds

(VOCV)

Revision Date 03.01.2020

according to Regulation (EC) No. 1907/2006

# **Everbuild Technic Hybriflex SMP**







Print Date 03.01.2020

Version 2.0

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Not applicable

no VOC duties

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations

(COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### **SECTION 16: Other information**

### **Full text of H-Statements**

H226 : Flammable liquid and vapour. H317 : May cause an allergic skin reaction.

H332 : Harmful if inhaled. H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Flam. Liq. : Flammable liquids Skin Sens. : Skin sensitisation

2006/15/EC : Europe. Indicative occupational exposure limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2006/15/EC / TWA : Limit Value - eight hours

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration
GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

Revision Date 03.01.2020

according to Regulation (EC) No. 1907/2006

# **Everbuild Technic Hybriflex SMP**







period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

### **Further information**

Classification of the mixture: Classification procedure:

Skin Sens. 1 H317 Calculation method Aquatic Chronic 3 H412 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GB / EN