

Feb® Wintamix

DECLARATION OF PERFORMANCE

No. 23260444

| 1 | UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE: | FBWINTA |
|----|---|--|
| 2 | INTENDED USE/S | As an air entraining/plasticising admixture for mortar |
| 3 | MANUFACTURER: | Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Industrial Estate Leeds, LS9 OSW |
| 4 | AUTHORISED REPRESENTATIVE: | N/A |
| 5 | SYSTEM/S OF AVCP: | 2+ |
| 6a | HARMONISED STANDARD: | EN934-3:2009 |
| - | Notified body/ies: | 0120 |

7 DECLARED PERFORMANCE/S

| Essential Characteristics | Performance | AVCP | Technical Specification |
|---------------------------|---|------|----------------------------|
| Chloride ion content | <0.1 % w/w | | |
| Alkali content | <1 % w/w | | |
| Corrosion behavior | Contains only components from EN934-1:2008 annex A1 | | |
| Compressive strength | Test mix >70 % of control | | |
| Water reduction | ≥8 % by mass | | |
| Air entrainment Initial | 14-20 % | | EN934-3:2009 |
| Air after 1 hour standing | ≥initial –3 % | | |
| Air after extended mixing | Initial ±5 % | | |
| Dangerous substances | See sds | | |

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Paul Thomas

Function: Technical Product

Coordinator

At Leeds on 18 June 2021

Name: Mariam Maqsood Function: Product Manager At Leeds on 18 June 2021

End of information as required by UKCA





| Everbuild Building Products LTD, Leeds, UK |
|--|
|--|

DoP No. 23260444

EN934-3:2009

Notified Body 0120

As an air entraining/plasticising admixture for mortar

| Alkali content<1 % w/w | Chloride ion content | <0.1 % w/w | |
|--|---------------------------|---------------------------|--|
| Corrosion benavior annex A1 Compressive strength Test mix >70 % of control Water reduction ≥8 % by mass Air entrainment Initial 14-20 % Air after 1 hour standing Air after extended mixing Initial ±5 % | Alkali content | <1 % w/w | |
| Water reduction ≥8 % by mass Air entrainment Initial 14-20 % Air after 1 hour standing ≥initial -3 % Air after extended mixing Initial ±5 % | Corrosion behavior | <i>,</i> | |
| Air entrainment Initial 14-20 % Air after 1 hour standing ≥initial −3 % Air after extended mixing Initial ±5 % | Compressive strength | Test mix >70 % of control | |
| Air after 1 hour standing ≥initial −3 % Air after extended mixing Initial ±5 % | Water reduction | ≥8 % by mass | |
| Air after extended mixing Initial ±5 % | Air entrainment Initial | 14-20 % | |
| | Air after 1 hour standing | ≥initial -3 % | |
| Dangerous substances See sds | Air after extended mixing | Initial ±5 % | |
| | Dangerous substances | See sds | |
| | | | |

www.everbuild.co.uk/downloads/

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

FBWINTA 23260444 2021/06, ver. 01 1213



1213

