

## TECHNICAL DATA

# Geocel® Painters Mate

## Flexible Acrylic Filler



**Geocel® Painters Mate Flexible Acrylic Filler** is a highly flexible acrylic sealant for use on internal and external surfaces including skirting boards, door and window frames, floorboards, ceilings, walls and plasterboard. Resists cracking, no sanding is required and can be overpainted approximately 1 hour after application.

- High performance acrylic
- For internal and external use
- Can be overpainted in 1 hour
- No sanding required

### SPECIFICATIONS

Manufactured under ISO 9001

### TECHNICAL DATA

<b>Storage Life</b>	24 months stored in original containers between 4°C and 25°C
<b>Colour</b>	White, Brown, Magnolia
<b>Skin Time</b>	30 - 45 minutes

**Specification writers:** These values are not intended for use in preparing specifications. Please contact your local **Geocel®** Sales Representative prior to writing specifications on this product.

### APPLICATION

Ensure gaps or cracks to be filled are free from dust, dirt and grease and surfaces are dry. Deep gaps should be half filled with tissue paper before application.

Remove nozzle and cut tip to required width. Place cartridge in cartridge gun and apply material into gap or crack to be filled.

Ensure **Geocel® Painters Mate Flexible Acrylic Filler** makes full contact with sides and back of the joint. Smooth surface lightly with a damp cloth after application.

### PACKAGING

**Geocel® Painters Mate Flexible Acrylic Filler** is supplied in 310ml cartridges packed in boxes of 12.



### HEALTH AND SAFETY

Health and Safety data sheets available on request.

### TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact **Geocel®** Technical Service.

**IMPORTANT NOTE:** The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Geocel's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Geocel's sole warranty is that the product will meet the Geocel sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Geocel specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Geocel disclaims liability for any incidental or consequential damage.