

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

Sika® Aktivator



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : Sika® Aktivator

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Not available.

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Distributor** : Sika Limited  
Watchmead Welwyn Garden City  
Hertfordshire. AL7 1BQ  
United Kingdom

**Town/City and Post Code** :

**Telephone no.** : 01707 394444

**Fax no.** : 01707 329129

**e-mail address of person responsible for this SDS** : EHS@uk.sika.com

**Emergency telephone number** : +44 (0)1707 363899 (available during office hours).

### 1.4 Emergency telephone number

#### Supplier

Telephone number : +44 (0)1707 363899 (available during office hours).

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : F; R11  
Xn; R65  
Xi; R38  
R43, R67  
N; R50/53

**Physical/chemical hazards** : Highly flammable.

**Human health hazards** : Harmful: may cause lung damage if swallowed. Irritating to skin. May cause sensitisation by skin contact. Vapours may cause drowsiness and dizziness.

**Environmental hazards** : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Hazard symbol or symbols :



**Indication of danger** : Highly flammable, Harmful, Dangerous for the environment

**SECTION 2: Hazards identification**

<b>Risk phrases</b>	: R11- Highly flammable. R65- Harmful: may cause lung damage if swallowed. R38- Irritating to skin. R43- May cause sensitisation by skin contact. R67- Vapours may cause drowsiness and dizziness. R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<b>Safety phrases</b>	: S24- Avoid contact with skin. S37- Wear suitable gloves.
<b>Hazardous ingredients</b>	: N-(3-(Trimethoxysilyl)propyl)ethyldiamin
<b>Supplemental label elements</b>	: Not applicable.

**2.3 Other hazards**

**Other hazards which do not result in classification** : Not available.

**SECTION 3: Composition/information on ingredients**

<b>Substance/mixture</b>	: Mixture
<b>Chemical family/Characteristics</b>	: Bonding agent, containing solvent

Product/ingredient name Identifiers	%	<b>Classification</b>		Type
		67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
Naphtha (Erdöl), mit Wasserstoff behandelte leichte EC: 265-151-9 CAS: 64742-49-0 Index: 649-328-00-1	>= 50 - < 75	F; R11  Xn; R65 Xi; R38 R67 N; R51/53	Flam. Liq. 2, H225  Skin Irrit. 2, H315 STOT SE 3, H336i Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1]
Heptan EC: 205-563-8 CAS: 142-82-5 Index: 601-008-00-2	>= 25 - < 35	F; R11 Xn; R65 Xi; R38 R67 N; R50/53	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	[1] [2]
Tris(dodecylbenzolsulfonato-O)(propan-2-olato)titan EC: 262-777-4 CAS: 61417-55-8	>= 1 - < 3	Xn; R22  Xi; R36/37/38	Acute Tox. 4, H302  Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335i	[1]
N-(3-(Trimethoxysilyl)propyl)ethyldiamin EC: 217-164-6 CAS: 1760-24-3	>= 1 - < 2.5	Xn; R20 Xi; R41 R43 N; R51/53 <b>See section 16 for the full text of the R-phrases declared above</b>	Acute Tox. 4, H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411 <b>See Section 16 for the full text of the H statements declared above.</b>	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

## SECTION 3: Composition/information on ingredients

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- |                                   |  |
|-----------------------------------|--|
| <b>Eye contact</b>                | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.  |
| <b>Inhalation</b>                 | : If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Get medical attention if adverse health effects persist or are severe. Get medical attention if symptoms appear.           |
| <b>Skin contact</b>               | : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention if symptoms occur. |
| <b>Ingestion</b>                  | : Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. Maintain an open airway. Seek immediate medical attention.   |
| <b>Protection of first-aiders</b> | : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.  |

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- |                     |  |
|---------------------|--|
| <b>Eye contact</b>  | : May cause eye irritation.  |
| <b>Inhalation</b>   | : Vapours may cause drowsiness and dizziness. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. |
| <b>Skin contact</b> | : Irritating to skin. May cause sensitisation by skin contact.   |
| <b>Ingestion</b>    | : Aspiration hazard if swallowed. Can enter lungs and cause damage. Irritating to mouth, throat and stomach.   |

#### Over-exposure signs/symptoms

- |                     |  |
|---------------------|--|
| <b>Eye contact</b>  | : No specific data.  |
| <b>Inhalation</b>   | : Adverse symptoms may include the following:<br>nausea or vomiting<br>headache<br>drowsiness/fatigue<br>dizziness/vertigo |
| <b>Skin contact</b> | : Adverse symptoms may include the following:<br>irritation<br>redness   |
| <b>Ingestion</b>    | : Adverse symptoms may include the following:<br>nausea or vomiting  |

### 4.3 Indication of any immediate medical attention and special treatment needed

- |                            |   |
|----------------------------|---|
| <b>Notes to physician</b>  | : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| <b>Specific treatments</b> | : No specific treatment.  |

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Highly flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
sulfur oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. This material is very toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment.

**Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment.

**SECTION 6: Accidental release measures**

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**7.2 Conditions for safe storage, including any incompatibilities**

- : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

**7.3 Specific end use(s)**

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limits**

Product/ingredient name	Exposure limit values
Heptan	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007).</b> TWA: 500 ppm 8 hour(s).
Ethanol	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007).</b> TWA: 1920 mg/m <sup>3</sup> 8 hour(s). TWA: 1000 ppm 8 hour(s).

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

## SECTION 8: Exposure controls/personal protection

### Derived effect levels

No DELs available.

### Predicted effect concentrations

No PECs available.

### 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Reference number EN 374. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves. (0,4 mm), breakthrough time <30 min. Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapour filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.

**Colour** : Colourless to light yellow.

**Odour** : Hydrocarbon.

**Odour threshold** : Not available.

**pH** : Not available.

**Melting point/freezing point** : Not available.

**Initial boiling point and boiling range** : 78°C

**Flash point** : Closed cup: -4°C

**Evaporation rate** : Not available.

**SECTION 9: Physical and chemical properties**

<b>Flammability (solid, gas)</b>	: Not available.
<b>Burning time</b>	: Not applicable.
<b>Burning rate</b>	: Not applicable.
<b>Upper/lower flammability or explosive limits</b>	: Lowest known value: Lower: 1.1% (Naphtha (Erdöl), mit Wasserstoff behandelte leichte) Highest known value: Upper: 19% (Ethanol)
<b>Vapour pressure</b>	: Highest known value: 5.8 kPa (43.5 mm Hg) (ethanol)
<b>Vapour density</b>	: Not available.
<b>Density</b>	: ~0.71 g/cm <sup>3</sup> [20°C (68°F)]
<b>Relative density</b>	: Not available.
<b>Solubility(ies)</b>	: Not available.
<b>Partition coefficient: n-octanol/water</b>	: Not available.
<b>Auto-ignition temperature</b>	: 285°C (heptan)
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Kinematic (40°C): <0.069 cm <sup>2</sup> /s
<b>Explosive properties</b>	: Not available.
<b>Oxidising properties</b>	: Not available.

**9.2 Other information**

No additional information.

**SECTION 10: Stability and reactivity**

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: The product is stable.
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
<b>10.5 Incompatible materials</b>	: Highly reactive or incompatible with the following materials: oxidizing materials
<b>10.6 Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
N-(3-(Trimethoxysilyl)propyl)ethylenediamin	LC50 Inhalation Vapour	Rat	1.49 to 2.44 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	2400 mg/kg	-

**Conclusion/Summary** : Not available.**Irritation/Corrosion****Conclusion/Summary** : Not available.

**SECTION 11: Toxicological information****Sensitisation**

Conclusion/Summary : Not available.

**Mutagenicity**

Conclusion/Summary : Not available.

**Carcinogenicity**

Conclusion/Summary : Not available.

**Reproductive toxicity**

Conclusion/Summary : Not available.

**Teratogenicity**

Conclusion/Summary : Not available.

Information on the likely routes of exposure : Not available.

**Potential acute health effects**

Eye contact : May cause eye irritation.

Inhalation : Vapours may cause drowsiness and dizziness. May cause irritation.

Skin contact : Irritating to skin. May cause sensitisation by skin contact.

Ingestion : Aspiration hazard if swallowed. Can enter lungs and cause damage. Irritating to mouth, throat and stomach.

**Symptoms related to the physical, chemical and toxicological characteristics**

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigoSkin contact : Adverse symptoms may include the following:  
irritation  
rednessIngestion : Adverse symptoms may include the following:  
nausea or vomiting**Delayed and immediate effects and also chronic effects from short and long term exposure****Short term exposure**

Potential immediate effects : Not available.

Potential delayed effects : Not available.

**Long term exposure**

Potential immediate effects : Not available.

Potential delayed effects : Not available.

**Potential chronic health effects**

Not available.

Conclusion/Summary : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.



**SECTION 11: Toxicological information**

**Other information** : Not available.

**SECTION 12: Ecological information****12.1 Toxicity**

**Conclusion/Summary** : Not available.

**12.2 Persistence and degradability**

**Conclusion/Summary** : Not available.

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Heptan	4.66	-	high

**12.4 Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

**12.5 Results of PBT and vPvB assessment**

**PBT** : Not applicable.

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Product**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

**Hazardous waste** : packaging containing residues of or contaminated by dangerous substances

**European waste catalogue (EWC)**







Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

**Packaging** : Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and regulations.

**SECTION 14: Transport information**

	ADR/RID - ADN/ADNR	IMDG	IATA
14.1 UN number	UN1866	UN1866	UN1866
14.2 UN proper shipping name	Resin solution Heptanes	Resin solution Heptanes	Resin solution Heptanes
14.3 Transport hazard class(es)	3  	3  	3  
14.4 Packing group	II	II	II
14.5 Environmental hazards	Yes.	Yes.	Yes.
14.6 Special precautions for user	Not available.	Not available.	Not available.
Additional information	-	<b>Emergency schedules (EmS)</b> F-E, S-E	-
Classification code	F1		

14.7 Transport in bulk : Not available.  
according to Annex II of  
MARPOL 73/78 and the IBC  
Code

**SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions** : Not applicable.  
on the manufacture,  
placing on the market and  
use of certain dangerous  
substances, mixtures and  
articles

**VOC content (EU)** : VOC (w/w): 94.19%

Other EU regulations

**REACH Information:** : All substances contained in Sika Products are  
- preregistered or registered by our upstream suppliers, and/or  
- preregistered or registered by Sika, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

**Europe inventory** : All components are listed or exempted.

**SECTION 15: Regulatory information**

<b>References</b>	: Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (CHIP 4) Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as amended) Health & Safety at Work Act 1974 Dangerous Substances and Explosive Atmospheres Regulations 2002 (DSEAR) The Environmental Protection (Duty of Care) Regulations 1991  Hazardous waste regulations 2005 The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007
<b>Guidance Publications</b>	: Approved Code of Practice - Management of Health and Safety at Work, HSE General Approved Code of Practice to COSHH Regulations, HSE. EH40, Workplace Exposure Limits, HSE (as updated). HS(G) 53, Respiratory Protection Equipment - a Practical Guide for Users, HSE.
<b>15.2 Chemical Safety Assessment</b>	: This product contains substances for which Chemical Safety Assessments are still required.

**SECTION 16: Other information**

Indicates information that has changed from previously issued version.

<b>Abbreviations and acronyms</b>	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number
<b>Full text of abbreviated H statements</b>	: H225 Highly flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335i May cause respiratory irritation. H336 May cause drowsiness or dizziness. H336i May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Aquatic Acute 1, H400 AQUATIC TOXICITY (ACUTE) - Category 1 Aquatic Chronic 1, H410 AQUATIC TOXICITY (CHRONIC) - Category 1 Aquatic Chronic 2, H411 AQUATIC TOXICITY (CHRONIC) - Category 2 Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 2, H225 FLAMMABLE LIQUIDS - Category 2 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1 STOT SE 3, H335i SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE): INHALATION [Respiratory tract irritation] - Category 3  STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Narcotic effects] - Category 3  STOT SE 3, H336i SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE): INHALATION [Narcotic effects] - Category 3

**SECTION 16: Other information**

**Full text of abbreviated R phrases** : R11- Highly flammable.  
 R20- Harmful by inhalation.  
 R22- Harmful if swallowed.  
 R65- Harmful: may cause lung damage if swallowed.  
 R41- Risk of serious damage to eyes.  
 R38- Irritating to skin.  
 R36/37/38- Irritating to eyes, respiratory system and skin.  
 R43- May cause sensitisation by skin contact.  
 R67- Vapours may cause drowsiness and dizziness.  
 R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Full text of classifications [DSD/DPD]** : F - Highly flammable  
 Xn - Harmful  
 Xi - Irritant  
 N - Dangerous for the environment

**History**

**Date of printing** : 22.06.2011.  
**Date of issue** : 22.06.2011.  
**Date of previous issue** : 23.09.2010.

**Notice to reader**

*The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.*