



EN 15651-4:2012

13

1213

DECLARATION OF PERFORMANCE

Sikaflex® PRO-3 SL

| | | | | | | | |
|----|----|----|----|-----|-------|----|------|
| 02 | 05 | 05 | 01 | 100 | 00000 | 11 | 1009 |
|----|----|----|----|-----|-------|----|------|

Declaration of Performance

| | |
|---|--|
| 1. Product Type: Unique identification code of the product-type: | EN 15651-4:2012, Type PW EXT-INT CC Sikaflex® PRO-3 SL |
| 2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): | See packaging of the product |
| 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: | Sealant for movement joints in floors for interior and exterior application (intended for use in cold climates) |
| 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): | Sikaflex PRO-3 SL Sika Services AG TM Sealing & Bonding Tüffenwies 16 8048 Zürich Switzerland |
| 5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): | Not relevant |
| 6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V: | System 3 for the type testing System 3 for the reaction to fire testing |
| 7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard: | The notified body SKZ Tecona GmbH, identification number 1213, performed the type testing and the testing of the reaction to fire and issued test report and classification report. |
| 8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued: | Not relevant |



9. Declaration of Performance

Conditioning: Method B
Substrate: Mortar M1, Sika® Primer-3 N

| Essential characteristics | Performance | Test standard | Harmonised technical specification |
|---|-------------------------------------|---|------------------------------------|
| Reaction to fire | Class E | EN ISO 13238 Classification acc. EN 13501-1:2010 | EN 15651-4:2012 |
| Release of chemicals dangerous to the environment and health | NPD | EN 15651-4:2012; 4.5 | |
| Water tightness and air tightness | | | |
| • Tensile properties at maintained extension | NF | EN ISO 8340 | |
| • Loss of volume | ≤10% | EN ISO 10563 | |
| • Tear resistance | NF | EN 15651-4:2012; 4.3.2.6 | |
| • Adhesion/cohesion properties at maintained extension after 28 days water immersion | NF Change of secant modulus <50% | EN 15651-4:2012; 4.4.1 | |
| • Adhesion/cohesion properties at maintained extension after 28 days salt water immersion | NF Change of secant modulus <50% | EN 15651-4:2012; 4.4.1 | |
| • Tensile properties at maintained extension at -30°C | NF | EN ISO 8340 modified | |
| Durability | pass | EN ISO 8339 EN ISO 8340 EN ISO 9047 EN ISO 10590 | |



10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Ralf Heinzmann
Global Technical Manager
Sika Services AG
TM Sealing & Bonding



Christian Völm
Corporate Product Engineer
Sika Services AG
TM Sealing & Bonding

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.



Sealing & Bonding
Declaration of Performance
Identification No.
Edition
Version No.

020505011000000011
06.2013
V1



1213

1009

13

02 05 05 01 100 00000 11

EN 15651-4:2012

Sealant for movement joints in floors for interior and exterior application
(intended for use in cold climates)
PW EXT-INT CC

Conditioning: Method B
Substrate: Mortar M1, Sika® Primer-3 N

| Essential characteristics | Performance |
|---|-----------------------------------|
| Reaction to fire | Class E |
| Release of chemicals dangerous to the environment and health | NPD |
| Water tightness and air tightness | |
| • Tensile properties at maintained extension | NF |
| • Loss of volume | ≤ 10 % |
| • Tear resistance | NF |
| • Adhesion/cohesion properties at maintained extension after 28 days water immersion | NF, change of secant modulus <50% |
| • Adhesion/cohesion properties at maintained extension after 28 days salt water immersion | NF, change of secant modulus <50% |
| • Tensile properties at maintained extension at -30°C | NF |
| Durability | pass |

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



For further Information
Sika Services AG
TM Sealing & Bonding
Tuffenwies 16
8048, Zurich
Switzerland

+41 58 436 40 40
www.sika.com