according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor® 122 Level

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Floor levelling compound

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person : EHS@uk.sika.com

responsible for the SDS

1.4 Emergency telephone number

+44 (0)1707 363899 (available during office hours).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Category 1A H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

T. E.

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

container or label at hand.

P102 Keep out of reach of children.

Prevention:

P260 Do not breathe dust or mist.

according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level



Revision Date 10.09.2019 Version 9.3

Print Date 01.10.2019

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do

NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance

with local regulation.

Hazardous components which must be listed on the label:

Cement (chromium reduced)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration		
	EC-No.		(% w/w)		
	Registration number				
Cement (chromium reduced)	65997-15-1	Skin Irrit. 2; H315	>= 10 - < 20		
	266-043-4	Eye Dam. 1; H318			
		STOT SE 3; H335			
Substances with a workplace exposure limit :					
Quartz (SiO2)	14808-60-7		>= 50 - <= 100		
	238-878-4				

according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level



Revision Date 10.09.2019 Version 9.3 Print Date 01.10.2019

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : Health injuries may be delayed.

corrosive effects

Causes serious eye damage.


Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level



SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for firefighters

ucts

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Pick up and arrange disposal without creating dust.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level

Revision Date 10.09.2019



Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Further information on stor-

age stability

: Keep in a dry place. No decomposition if stored and applied

as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Quartz (SiO2)	14808-60-7	TWA (Respirable dust)	0,1 mg/m3 (Silica)	GB EH40
Further information	those fractions of undertaken in action and thoracic and inhalmation in air equition dust or 4 mg.m-dust will be subjected. Some dust will be subjected. Some dust must comparticles of any particular and the body resparticle. HSE distermed 'inhalable fraction of airbor breathing and is Respirable dust exchange region are given in MDI own assigned W	s of these limits, resping airborne dust which coordance with the meas for sampling and gralable aerosols, The Galth includes dust of a al to or greater than 138-hour TWA of respect to COSHH if peopests have been assigned with the appropriate wide range of sizes, particle after entry interpretable and 'respirable', Interpretable and 'respirable', Interpretable for approximates to the for of the lung. Fuller de HS14/4., Where dusts (EL, all the relevant lirtic short-term exposur	will be collected whethods described in avimetric analysis of COSHH definition of any kind when prese 0 mg.m-3 8-hour Thirable dust. This meded specific WELs are telimits., Most industrated to the human respirate to the human respirate to the human respirate the nose and mount of deposition in the respondent of the praction of the present of the pre	nen sampling is MDHS14/4 respirable, for a substance ent at a concention. WA of inhalable ans that any just above these and exposure to estrial dusts concestion and fate atory system, eand size of the ing purposes imates to the just during espiratory tract, test to the gas just atory material test that have their olied with.

according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level



Print <u>Date 01.10.2019</u>

Revision Date 10.09.2019 Version 9.3

	the long term av	raccura limit abould be	a upod			
Limostono		posure limit should be		GB EH40		
Limestone	1317-65-3	TWA (inhalable dust)	10 mg/m3			
Further information		s of these limits, respi				
		those fractions of airborne dust which will be collected when sampling is				
		ccordance with the me				
		s for sampling and gra				
		alable aerosols, The (
		alth includes dust of a				
	tration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable					
	dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any					
		ect to COSHH if peop				
		sts have been assign				
		ply with the appropria				
		a wide range of sizes.				
		particle after entry int				
		sponse that it elicits, d stinguishes two size fr				
		e' and 'respirable'., Inf				
		rne material that enter				
		therefore available for				
		approximates to the f				
		n of the lung. Fuller de				
		are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with.,				
		ic short-term exposur				
the long-term exposure limit should be used.				,		
	-	TWA (Respirable	4 mg/m3	GB EH40		
		dust)				
Further information		s of these limits, respi				
		of airborne dust which				
	undertaken in accordance with the methods described in MDHS14/4					
	General methods for sampling and gravimetric analysis or respirable,					
	thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concen-					
	tration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any					
		ect to COSHH if peop				
	levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts con-					
	tain particles of a wide range of sizes. The behaviour, deposition and fate					
	of any particular particle after entry into the human respiratory system,					
	and the body response that it elicits, depend on the nature and size of the					
	particle. HSE distinguishes two size fractions for limit-setting purposes					
	termed 'inhalable' and 'respirable'., Inhalable dust approximates to the					
	fraction of airborne material that enters the nose and mouth during					
	breathing and is therefore available for deposition in the respiratory tract.					
	Respirable dust approximates to the fraction that penetrates to the gas					
	exchange region of the lung. Fuller definitions and explanatory material					
	are given in MDHS14/4., Where dusts contain components that have their					
own assigned WEL, all the relevant limits should be complied						
		ic short-term exposur		gure three times		
		posure limit should be		T == .		
Cement (chromium reduced)	65997-15-1	TWA (inhalable	10 mg/m3	GB EH40		
F 0 16 0	F (1	dust)		<u> </u>		
Further information	For the purposes of these limits, respirable dust and inhalable dust are					
	those fractions of airborne dust which will be collected when sampling is					
	ertaken in accordance with the methods described in MDHS14/4					
	General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance					
	inoracic and inha	aiable aerosois, The C	JUSHIT GETINITION O	ı a substance		

according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level



Revision Date 10.09.2019 Version 9.3 Print Date 01.10.2019

	-	
	hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.	
	TWA (Respirable 4 mg/m3 GB EH40 dust)	
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.	

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields

Eye wash bottle with pure water Wear eye/face protection.


Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level





Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Skin and body protection : Dust impervious protective suit

> Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

particulate filter P

P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance powder

Colour grey

Odour odourless

Odour Threshold No data available

pН : > 12

Concentration: 500 g/l

Melting point/range / Freezing : No data available

point

Boiling point/boiling range : No data available

Not applicable Flash point

No data available Evaporation rate

Flammability (solid, gas) : No data available

according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level

Revision Date 10.09.2019 Version 9.3 Print Date 01.10.2019

Upper explosion limit / Upper : No data available

flammability limit

Lower explosion limit / Lower : No data available

flammability limit

Vapour pressure : No data available

Relative vapour density : No data available

Density : 1,4 g/cm3 (20 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

: No data available Auto-ignition temperature

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Explosive properties : No data available

: No data available Oxidizing properties

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level

Revision Date 10.09.2019 Version 9.3



10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

•

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

No data available

according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level

Revision Date 10.09.2019 Version 9.3 Print Date 01.10.2019



12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 16 03 03* inorganic wastes containing dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level

Revision Date 10.09.2019 Version 9.3



14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

None of the components are listed

(=> 0.1 %).

: Not applicable

: Not applicable

Not applicable

Not applicable

Not applicable

Not applicable

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level

Revision Date 10.09.2019



Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV) no VOC duties

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations

(COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

Other regulations:

This product contains cement. Wet cement or mortar may cause alkali burns if in direct and/or prolonged contact with the skin. Wear protective clothing at all times when working with cement based products.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.
H318 : Causes serious eye damage.
H335 : May cause respiratory irritation.

Full text of other abbreviations

Eye Dam. : Serious eye damage

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration
GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

according to Regulation (EC) No. 1907/2006

Sikafloor® 122 Level



Revision Date 10.09.2019 Version 9.3 Print Date 01.10.2019

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Skin Corr. 1A H314 On basis of test data. Eye Dam. 1 H318 On basis of test data.

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GB / EN